

25X bare wire Noble metal element thermocouple



Overview

A high temperature Noble metal thermocouple, elements are provided to match the ITS 1990 curve. 24 gauge (0.020") wire is standard with other gauges available. Spools of bare platinum wire are also available.

Technical specification

Feature	Description
Model number	253R, 252S, 255B, 257C - no insulator provided
Sensor type	High temperature Noble metal
ANSI calibration	R, S, B, C
Accuracy	Standard limits of error, special limits of error (reference grade)
Number of circuits	1
Termination	Bare strip
Accessory	Insulator in alumina, mullite or hafnia

About Ultra Energy

Organizations working with nuclear and industrial technologies must deliver reliable production at the same time as safeguarding people, the environment and infrastructure. We develop and manufacture measurement and control solutions that give our customers complete, long-term control over systems operating in harsh environments, helping them operate safely and increasing the value derived from their investments over their total lifespan.

Part of Curtiss-Wright, Ultra Energy has worked with nuclear and industrial customers for over 60 years. We support customers across the world from facilities located in the US and UK. Our solutions are embedded in strategic national infrastructure and our people are active partners in customer programs that are focused on delivering advanced future nuclear and industrial capabilities.

United States of America

707 Jeffrey Way
Round Rock
Texas 78665-2408
USA

Tel: +1 512-434-2800

United Kingdom

Innovation House
Lancaster Road
Ferndown Industrial Estate
Wimborne
Dorset BH21 7SQ
UK

Tel: +44 (0) 1202 850 450

For more information

Web: ultra.energy

Email: sales@ultra.energy